


FG-32

DDC Energy Controller, Internet and Cloud Ready

- ❖ ARM 9 S3C2410 200MHz Main Processor
- ❖ M3 Cortex Processor for the I/O
- ❖ 16 Mbyte NOR Flash
- ❖ 64 Mbyte SDRAM
- ❖ SD Card Reader for Histories and Graphics
- ❖ 1 x 10/100 Ethernet Port
- ❖ 1 x Mini USB
- ❖ 2 x RS485
- ❖ RTC
- ❖ SuperCap Apps Safety Backup
- ❖ 24V AC/DC Power
- ❖ Hardware Security ID
- ❖ 16 x UI
- ❖ 8 x DO/LED for Status
- ❖ 8 x UO (200mA sink for Switching Relays)
- ❖ Remote Flash Upgrades
- ❖ HTML5 Web Server on Board!



The new FG series of Open Automation Controllers from EasyIO are the new range of Internet ready Field Controllers. They comprise of combined Area Controller capabilities and features, as well built in I/O, and huge data logging capacity, all packaged as the future solution for the Internet of things, in Energy and Building Facility Control. The Controller also supports multi concurrent protocols and services such as BACnet, Modbus, TCOM, Web Services, and both Server and Client services.

This new range complies with the 'Internet of Things' by interfacing directly to Cloud Services, without an additional Gateway, or Server. To power the application, The FG has a dual ARM processor engine, and also a built-in Web Server.

The FG series change the way that we will deploy Building Automation, especially in multiple Facilities and locations, whereby, a starter package can be deployed quickly, and cost effectively, without any additional hardware or middleware. We see this range of FG Controllers allowing us and the industry to extend their reach deeper and wider into all kinds of Energy Performance Solutions. Ranging from Retail Stores, Schools, and Residential, Smart Grid and so on.

Another exciting feature, is the openness, and its web friendly tools to enable 3rd Party Tools to be deployed in addition to the Workbench that we are all familiar with today. This platform will meet the needs of simple controls requirements and complex HVAC plants, such as Chiller Sequencing and Roof Top Control. Truly a welcome change!

Graphics will also be served from the FG Engine, nicely embedded in the Linux OS. To compliment this there will be third party Graphics Tools that will be used to design and implement Graphic Screens, the content being stored in the built-in micro SD Card slot (up to 16GB).

Features

- ❖ Power! - TWO ARM processors
- ❖ Memory/Storage - SD Card and massive history storage
- ❖ Supports BACnet, TCOM, Modbus and Web Services
- ❖ Fills a Gap in the market, between an Area Controller and the EasyIO 30P controller
- ❖ Html5 Graphics! - IPAD friendly

Specifications

- ❖ ARM 9 S3C2410 200MHz Main Processor
- ❖ M3 Cortex Processor for the I/O
- ❖ 16 Mbyte NOR Flash
- ❖ 64 Mbyte SDRAM
- ❖ SD Card Reader
- ❖ 1 x 10/100 Ethernet Port
- ❖ 1 x Mini USB
- ❖ 2 x RS485
- ❖ RTC
- ❖ SuperCap Apps Backup
- ❖ 24V AC/DC Power
- ❖ Hardware Security ID

Device Info

Model	EasyIO-FG-32
Description	EasyIO-FG32 Sedona series: 32 I/O Controller
Name	FG32 DDC

Device Specifications

Mechanical	Dimensions	9.2 in x 4.9 in x 1.7 in (233 mm x 124 mm x 44 mm)
	Material	UL Approved Plastic
	Weight	700g
Electrical	Power Supply	24V AC +/- 5% or 24V DC +20%/-15%
	Consumption	TBC
	Operating Temp	32 to 150 Deg-F (0 to 65 Deg-C)
	Storage Temp	-4 to 150 Deg-F (-20 to 65 Deg-C)
	Operating Humidity	10% to 95% relative humidity non-condensing
Inputs & Outputs	UO: 3 modes. Voltage mode, output range: 0-10V; Current mode, output range: 0-20mA; Digital mode, maximum sinking current: 200mA	
	UI: 5 modes: Digital mode, voltage free contact input, Resistance mode, input range: 500-500Kohm; Voltage mode, input range: 0-10V; Current mode, input range: 0-20mA; Pulse count mode, maximum pulse frequency: 20Hz	
	DO: Relay output with contact rating 1A 30VDC	

Communication

Physical Interface 1 & 2 (Port 1 & 2)	EIA-485 (BUS A, B) Two-wire, Half Duplex
Modbus Baud Rate	Speed: (9.6K, 19.2k, 38.4K, 57.6K, 115.2K bit/s), Data Bit: (8 bits), Parity: (None, Even, Odd)
Bacnet Baud Rate	Speed: (9.6K, 19.2k, 38.4K, 76.8K), Data Bit: (8 bits), Parity: (None)
Ethernet Support	IP, TCP, UDP, ICMP, HTTP, FTP
Application Support	Sox and TCOM driver

EasyIO Holdings Pte Ltd
www.EasyIO.com

CE, FCC and UL Pending



All specifications subject to change without notice or liability to provide changes to prior purchasers. Information and specifications published here are current as of the date of publication of this document. EasyIO Holdings, reserves the right to change or modify specifications without prior notice. The latest product specifications can be found by contacting our corporate headquarters, Singapore. Products or features contained herein may be covered by one or more U.S. or foreign patents. All brands and product names are trademarks or registered trademarks of their respective owners. Copyright © 2013 all rights reserved, EasyIO Holdings.